



H781MB 196.
RUS

ЛЕКСУС ЕКАТЕРИНБУРГ (343) 22-22-300



014



JT:JBAMCA402131144



EHL

C/TR /EA24
223 /A7TM /U661F
PLANTQ12

014 24

TOYOTA MOTOR CORPORATION
TC RU E-JP M102:00265
JTJBAMCA402L31144
2575 kg
4075 kg
1-1360kg
2-1590kg

MODEL AGL25L-AWTGZW

TYRES, 轮胎 PNEUMATIQUES
ШИНЫ-ЭКСПЛУАТАЦИОННЫЕ ХАРАКТЕРИСТИКИ

Cold tyre inflation pressure 轮胎气压
Pression des pneus à froid
Давление воздуха в холодных шинах

	kPa (bar)	
		
	235/65R18 106V	
160km/h~	260 (2.6)	260 (2.6)
~160km/h	250 (2.5)	250 (2.5)
	235/55R20 102V	
160km/h~	300 (3.0)	300 (3.0)
~160km/h	230 (2.3)	230 (2.3)

Compact spare tyre
小型备用轮胎
Pneu de secours compacte
Компактное запасное колесо
T165/90D18 107M 420(4.2)

SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
有关其他信息请参见用户手册
POUR DE PLUS AMPLES DETAILS VOIR LE MANUEL DU PROPRIETAIRE
ДОПОЛНИТЕЛЬНУЮ ИНФОРМАЦИЮ СМ.
В РУКОВОДСТВЕ ДЛЯ ВЛАДЕЛЬЦА.

48B80

K2





RX300



H781MB 196.
RUS 

 ЛЕКСУС - ЕКАТЕРИНБУРГ (343) 22-22-300

LEXUS

RX300









Средний расход топлива
165041 km
P



Light control stalk with icons for headlights, fog lights, and AUTO. Includes a rotary switch for wiper control.

Wiper control stalk with icons for wiper speed and AUTO. Includes a rotary switch for wiper control.

Steering wheel left-side controls including volume (+/-), MODE, and a call button.

Steering wheel right-side controls including a call button and a central button with directional arrows.















ШИНОМОНТАЖ